

**FORM-TEK WINTER SPECIFICATION SHEET**

# FORM-TEK

**Biodegradable concrete release agent, made with 100% renewable products**

## DESCRIPTION

FORM-TEK WINTER is a ready-to-use low viscosity concrete form release agent suitable for very low temperatures.

This product is made from environmentally-friendly vegetable and animal products and is safer for workers.

## USAGE

FORM-TEK is specially formulated for **on-site** casting and **precast** concrete

FORM-TEK is ready-to-use from the container and can be used with most type of forms:

- |             |                         |
|-------------|-------------------------|
| ✓ Plywood   | ✓ Fibreglas             |
| ✓ Steel     | ✓ Plastic               |
| ✓ Aluminium | ✓ Resins and composites |

## ADVANTAGES

- ✓ Biodegradable product
- ✓ Specially formulated for very low temperatures
- ✓ Does not contain any solvent
- ✓ Does not contain any VOCs
- ✓ Eliminates concrete buildup on forms
- ✓ Leaves almost no residue on the surface
- ✓ May contribute to LEED credits
- ✓ Non-toxic product
- ✓ Can be safely used for work near water
- ✓ Safe to use and store
- ✓ Non flammable, non combustible
- ✓ Non-dangerous goods according to TDG

## FORM-TEK WINTER SPECIFICATION SHEET

### SPECIFICATIONS

|                    |                          |                      |              |
|--------------------|--------------------------|----------------------|--------------|
| Colour :           | Light yellow             | Odor:                | Light citrus |
| Density :          | 0,9 g/mL                 | Viscosity at 40 °C : | 8-12 cSt     |
| Flash point :      | ≥ 150 °C                 | VOCs :               | None         |
| Biodegradability : | Completely biodegradable | Pour point:          | -24 °C       |

### APPLICATION INFORMATION

- **This product can be used without restrictions at temperatures above -18 °C**
- **It is possible to use this product at temperatures below -18 °C during a few hours if it has been stored in a heated area prior to commencing work.**
- Clean surfaces before application
- Apply the product on the form in a fine layer
- Follow elementary safety rules during application
- This product is not compatible with rubber and Styrofoam

### AVAILABLE SIZES

- ✓ 1000 L totes
- ✓ 205 L drums
- ✓ 19 L pails

### STORAGE

- Follow local legislation regarding product storage
- Do not store with flammable materials or food product
- In its original packaging, the product has a shelf life of at least a year



745 Pierre-Tremblay blvd  
St-Jean-sur-Richelieu, Qc, Canada,  
J2X 5G5  
Tel : 450-346-2463  
Fax : 888-623-2554  
[www.innoltek.com](http://www.innoltek.com)  
[info@innoltek.com](mailto:info@innoltek.com)

#### Revision 190404 FORM-TEK WINTER

Legal notice Product is reserved for a professional usage.

-Information in this document, especially recommendations regarding application and usage are supplied in good faith on the basis of experience INNOLTEK has to the date this document is written with the product when it is used, stored and generally handled in normal conditions. In application, differences in materials, concrete and site-specific conditions are so that no warranty is implied other than the legal warranty on the product itself. Please do not hesitate to contact INNOLTEK for more information on your specific situation before ordering. INNOLTEK will not recognize any responsibility in the event that the product has not been used according to our recommendations. Please make sure you have the latest revision of this document. It can be obtained by contacting INNOLTEK